

# Power Supplies

## 1757920002G

### AC ATX 200 W Power Supply



| Specifications                     |   |      |       |       |       |        |
|------------------------------------|---|------|-------|-------|-------|--------|
| Input                              | AC 100 ~ 240 V @ 47 ~ 63 Hz, full range (PFC) |      |       |       |       |        |
| Output                             | 200 W   |      |       |       |       |        |
|                                    | +3.3 V  | +5 V | -5 V  | +12 V | -12 V | +5 Vsb |
| Max. Load                          | 14 A  | 16 A | 0.2 A | 9 A   | 0.7 A | 1.5 A  |
| Min. Load                          | 0 A   | 2 A  | 0.1 A | 1 A   | 0.1 A | 0.1 A  |
| Safety                             | UL, TUV, CB, CCC                              |      |       |       |       |        |
| Compatible with Advantech products | 1757920002G: MIC-3039-B                       |      |       |       |       |        |

## 1757000190G/1757000011G

### AC cPCI 250 W Redundant Power Module/DC 48V cPCI 250 W Redundant Power Module



| Specifications                     |   |      |       |       |
|------------------------------------|---|------|-------|-------|
| Input                              | 1757000190G: AC 100 ~ 254 V @ 50 ~ 60 Hz, full range (PFC)<br>1757000011G: DC -48 V (-36 ~ -72 V input range) |      |       |       |
| Output                             | 250 W   |      |       |       |
|                                    | +3.3 V  | +5 V | +12 V | -12 V |
| Max. Load                          | 18 A  | 25 A | 5 A   | 0.5 A |
| Safety                             | 1757000190G: CSA, CB, CCC<br>1757000011G: CSA, CB   |      |       |       |
| Compatible with Advantech products | 1757000190G/1757000011G: MIC-3042/MIC-3043  |      |       |       |



1757000220G



1757000221G



## 1757000220G/1757000221G

### AC ATX 350 W Redundant Power Module

| Specifications                     |  |      |      |       |       |        |
|------------------------------------|--|------|------|-------|-------|--------|
| Input                              | AC 100 ~ 240 V @ 47 ~ 63 Hz, full range (PFC)  |      |      |       |       |        |
| Output                             | 350 W  |      |      |       |       |        |
|                                    | +3.3 V   | +5 V | -5 V | +12 V | -12 V | +5 Vsb |
| Max. Load                          | 35 A   | 35 A | -    | 8 A   | 0.8 A | 2 A    |
| Min. Load                          | 1 A  | 3 A  | -    | 0.5 A | 0 A   | 0 A    |
| Safety                             | UL, TUV, CB, CCC                               |      |      |       |       |        |
| Compatible with Advantech products | 1757000220G: MIC-3038<br>1757000221G: MIC-3041 |      |      |       |       |        |

## 1757000111G

### AC ATX 500 W Power Supply



| Specifications                     |   |       |       |       |       |        |
|------------------------------------|---|-------|-------|-------|-------|--------|
| Input                              | AC 115 ~ 240 V @ 47 ~ 63 Hz, full range (PFC) |       |       |       |       |        |
| Output                             | 500 W   |       |       |       |       |        |
|                                    | +3.3 V  | +5 V  | -5 V  | +12 V | -12 V | +5 Vsb |
| Max. Load                          | 30 A  | 40 A  | 0.8 A | 32 A  | 1 A   | 2 A    |
| Min. Load                          | 0 A   | 2.5 A | 0 A   | 1 A   | 0 A   | 0.1 A  |
| Safety                             | UL, TUV, CB, CCC                              |       |       |       |       |        |
| Compatible with Advantech products | 1757000111G: MIC-3081B                        |       |       |       |       |        |