


PER-V02B

Mini PCI TTL to DVI LCD Signal Conversion Module



Specifications

Form Factor	Mini PCI Type III A 2" x 2.35" (50.8 mm x 59.6 mm)
Signal Conversion Chipset	Silicon Image™ Sil1160CTU
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

Features

- **TTL to DVI LCD Signal Conversion**
- **Resolution up to 1600 x 1200**

Packing List

- TTL LCD Cable
- Quick Installation Guide
- PER-V02B

Ordering Information


- **TF-PER-V02B-A10**
Mini PCI, TTL to DVI LCD, Signal Conversion Module, Rev. A1.0

Optional Accessories

- **1700200200**
DVI Cable
- **1703400207**
TTL Cable for PFM-5301, PFM-5351, PFM-620S, GENE-6310B, GENE-6320, GENE-6350, PCM-6892A/B, PCM-6893, ETX-625

PER-V05V

Mini PCI Video Module



Specifications

Form Factor	Mini PCI Type III A 2" x 2.35" (50.8mm x 59.6mm)
Graphic Chipset	Volari™ Z9s (100Mhz)
Display	CRT output
Resolution	Up to 1600 x 1200 @85Hz
Power Requirement	+3.3V
Operating Temperature	32°F ~ 140°F (0°C ~ 60°C)

Features

- **Mini PCI Type III Interface**
- **One VGA output, Resolution Up to 1600 x 1200@85Hz**
- **Memory Size 32M DDRII**

Packing List

- D-Sub Cable
- Utility CD
- PER-V05V

Ordering Information

- **TF-PER-V05V-A10**
Mini PCI Video Module, Rev. A1.0