



WD RE4

Enterprise SATA Hard Drives

Ideal for servers, video surveillance, and other demanding write-intensive applications, WD RE4 7200 RPM Enterprise SATA hard drives offer up to 2 TB capacity, 64 MB cache, 4th generation vibration tolerance and 5-year limited warranty.



INTERFACE

SATA 3 Gb/s

WIDTH/HEIGHT

3.5-inch/1-inch

ROTATIONAL SPEED

7200 RPM

CAPACITIES

250 GB to 2 TB

MODEL NUMBERS

WD2003FYYS WD1003FBYX
WD1503FYYS WD5003ABYX

WD2503ABYX

Note: Not all products may be available in all regions of the world.

Product Benefits

Massive capacity

WD RE4 Enterprise SATA drives are available with up to 2 TB of cavernous capacity.

Dual processor

With double the processing power, WD RE4 boasts the highest performance of any drive in the WD RE family.

RAFF™

Enhanced RAFF technology includes sophisticated electronics to monitor the drive and correct both linear and rotational vibration in real time. The result is a significant performance improvement in high vibration environments over the previous generation of drives.

Dual actuator technology

A head positioning system with two actuators that improves positional accuracy over the data track(s). The primary actuator provides coarse displacement using conventional electromagnetic actuator principles. The secondary actuator uses piezoelectric motion to fine tune the head positioning to a higher degree of accuracy. (2 TB only)

StableTrac™

The motor shaft is secured at both ends to reduce system-induced vibration and stabilize platters for accurate tracking during read and write operations.

IntelliSeek™

Calculates optimum seek speeds to lower power consumption, noise, and vibration.

Multi-axis shock sensor

Automatically detects the subtlest shock events and compensates to protect the data.

RAID-specific, time-limited error recovery (TLER)

Prevents drive fallout caused by the extended hard drive error-recovery processes common to desktop drives.

NoTouch™ ramp load technology

The recording head never touches the disk media ensuring significantly less wear to the recording head and media as well as better drive protection in transit.

Thermal extended burn-in test

Each drive is put through extended burn-in testing with thermal cycling to ensure reliable operation.

Third generation dynamic fly height

Each read-write head's fly height is adjusted in real time for optimum reliability.

24x7 reliability

With 1.2 million hours MTBF (tested at 100% duty cycle), these drives have the highest available reliability rating on a high-capacity drive.

Applications

Ideal for servers, storage arrays, video surveillance, and other demanding applications.



WD RE4

Specifications ¹	2 TB	1.5 TB	1 TB	500 GB	250 GB
Model number	WD2003FYYS	WD1503FYYS	WD1003FBUYX	WD5003ABYX	WD2503ABYX
Interface	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s	SATA 3 Gb/s
Formatted capacity	2 TB	1.5 TB	1 TB	500 GB	251 GB
User sectors per drive	3,907,029,168	2,930,277,168	1,953,525,168	976,773,168	490,350,672
Native command queuing	Yes	Yes	Yes	Yes	Yes
SATA latching connector	Yes	Yes	Yes	Yes	Yes
Form factor	3.5-inch	3.5-inch	3.5-inch	3.5-inch	3.5-inch
Performance					
Data transfer rate (max)					
Buffer to host	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s	3 Gb/s
Host to/from drive (sustained)	138 MB/s	138 MB/s	128 MB/s	128 MB/s	128 MB/s
Cache (MB)	64	64	64	64	64
Rotational speed (RPM)	7200	7200	7200	7200	7200
Average drive ready time (sec)	21	21	18	14	14
Configuration/Organization					
Heads/disks	8/4	6/3	4/2	2/1	1/1
Bytes per sector (STD)	512	512	512	512	512
Reliability/Data Integrity					
Load/unload cycles ²	600,000	600,000	600,000	600,000	600,000
Non-recoverable read errors per bits read	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵	<1 in 10 ¹⁵
Limited warranty (years) ³	5	5	5	5	5
Power Management					
12VDC (A, max)	1.8	1.8	1.6	2.25	2.25
Average power requirements (W)					
Read/Write	10.7	10.7	7.9	6.4	6.4
Idle	8.2	8.2	5.9	4.5	4.5
Standby	1.3	1.3	0.7	0.8	0.8
Sleep	1.3	1.3	0.7	0.8	0.8
Environmental Specifications⁴					
Temperature (°C)					
Operating	5 to 55	5 to 55	5 to 55	5 to 55	5 to 55
Non-operating	-40 to 70	-40 to 70	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)					
Operating (2 ms, read/write)	30	30	30	30	30
Operating (2 ms, read)	65	65	65	65	65
Non-operating (2 ms)	300	300	300	350	350
Average acoustics (dBA) ⁵					
Idle mode	29	29	28	27	27
Performance seek mode	34	34	33	30	30
Quiet seek mode	30	30	29	29	29
Physical Dimensions					
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6	4/101.6	4/101.6
Weight (lb./kg, ± 10%)	1.66/0.75	1.66/0.75	1.49/0.68	0.99/0.45	0.99/0.45

¹As used for storage capacity, one megabyte (MB) = one million bytes, one gigabyte (GB) = one billion bytes, and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 3 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

²Controlled unload at ambient condition

³The term of the limited warranty may vary by region. Visit support.wdc.com/warranty for details.

⁴No non-recoverable errors during operating tests or after non-operating tests.

⁵Sound power level.

Western Digital, WD, the WD logo, and Put Your Life On It are registered trademarks in the U.S. and other countries; and NoTouch, IntelliSeek, StableTrac, RAFF, and FIT Lab are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product specifications subject to change without notice.

© 2010 Western Digital Technologies, Inc. All rights reserved.

Western Digital
20511 Lake Forest Drive
Lake Forest, California 92630
U.S.A.

2879-701338-A05 Sep 2010

For service and literature:

support.wdc.com
www.westerndigital.com

800.ASK.4WDC North America
800.832.4778 Spanish
+800.6008.6008 Asia Pacific
00800.27549338 Europe
+31.880062100 (toll free where available)
Europe/Middle East/Africa

