

The Most **Reliable** Storage For Industries

SU210-300





industrial.apacer.com



SU210-300

Overview

Apacer SU210-300 is a well-balanced solid-state disk (SSD) drive with compact form factor (JEDEC MO-300) and great performance. Designed in SATA 6.0 Gbps interface, the mSATA SSD is able to deliver exceptional read/write speed, making it the ideal companion for heavy-loading embedded or server operations with space constraints for host computing systems.

For data efficiency, the internal controlling unit of the mSATA SSD is engineered with DRAM for enhanced random performance. With Apacer's SLC-lite technology, the mSATA SSD performs with higher number of P/E cycles up to 20,000 times and comes with various implementations including powerful hardware ECC engine, power saving modes, wear leveling and flash block management.



Feature

- \cdot Built-in hardware ECC
- · Global Wear Leveling
- · SLC-lite Technology
- · Flash bad-block management
- · Flash Translation Layer: Page Mapping
- · S.M.A.R.T.
- · Power Failure Management
- · ATA Secure Erase
- · TRIM



industrial.apacer.com


Specifications


Model	SU210-300
Interface	SATA 3.0 (6Gb/s)
Connector	52 pin male
Form Factor	JEDEC MO-300
NAND Flash Type	MLC
Capacity	8GB~256GB
External DRAM	Yes
Sustained Read Performance (MB/sec)	Up to 525
Sustained Write Performance (MB/sec)	Up to 445
ECC Engine	Built-in 40-bit per 1K bytes BCH ECC
IOPS (4K Random Write)	79К
Standard Operating Temperature ($^{\circ}\text{C}$)	0 ~ + 70
Extended Operating Temperature (°C)	-40 ~ + 85
Storage Temperature (°C)	-40 ~ + 100
H/W Write Protect	Yes
Thermal Sensor	Yes
Shock	Operation: 50G, 11ms Non-operation: 1500G, 0.5ms
Vibration	Operation: 7.69 Grms, 20~2000 Hz/random (compliant with MIL-STD-810G) Non-operation: 4.02 Grms, 15 ~ 2000 Hz/sine (compliant with MIL-STD-810G)
Operating Voltage	3.3 V ± 5%
Power Consumption	Active mode: 785 mA / Idle mode: 105 mA
Dimension (L x W x H)	Without housing: 50.8 x 29.85 x 3.8mm
MTBF (hours)	>1,000,000




industrial.apacer.com

Mechanical Specification







Unit: mm

For more information, contact your Apacer representative

Global Presence Taiwan (Headquarters) Europe U.S.A. Apacer Technology Inc. Apacer Technology B.V. Apacer Memory America, Inc. Tel: +886-2-2267-8000 Tel: +31-40-267-0000 Tel: +1-408-518-8699 Fax: +886-2-2267-2261 Fax: +31-40-290-0686 Fax: 1-510-249-9551

Apacer Electronic(Shanghai) Co., Ltd. Tel: +86-21-6228-9939

Japan

Apacer Technology Corp. Tel: +81-3-5419-2668 Fax: +81-3-5419-0018

India Apacer Technologies Pvt. Ltd. Tel: +91-80-41529061~3 Fax: +91-80-41700215

China