

CompactFlash® Memory Card (CF) 303 Pro Series



The Cactus Technologies CompactFlash Memory Card (CF)

- **303 Pro Series** is a high capacity solid-state flash memory product that complies with the Personal Computer Memory Card International Association (PCMCIA) ATA (PC Card ATA) standard. In addition to the normal features found on the 303 Series CF, the Pro Series offers several security, purge, and write protect features. There is also a version with a physical write protect switch.

CACTUS CF PRO FEATURES

- ➔ **ATA SECURITY FEATURE SET:**
 - Set/Disable Password
 - Security Lock/Unlock
 - Additional Functions
- ➔ **CTPURGE: GENERIC ERASE OPTIONS:**
 - Erase Only
 - Erase and Overwrite with random data once
 - Erase and Overwrite with random data N times
- ➔ **CTPURGE: ERASE OPTIONS ACCORDING TO:**
 - USA-AF AFSSI 5020 spec
 - USA Navy NAVSO P-5239-26 spec
 - DoD 5220.22-M spec
 - NSA Manual 130-2 spec
 - USA-Army 380-19 spec
 - NISPOMSUP Chap.8, Sect.8-501 spec
 - IREC (IRIG) 106 specification
 - Others upon customer request
- ➔ **CTLOCK: SIMPLIFIED LOCK/UNLOCK COMMAND**
- ➔ **CTWPROT - WRITE PROTECT:**
 - Software Command
 - Hardware selection (CF pin 40)
 - Physical Write Protect Switch



PERFORMANCE

Read Data Transfer Rate

up to 35MB/sec

Write Data Transfer Rate

up to 20MB/sec



RELIABILITY

- Advanced Wear Leveling Algorithm
- Error Checking & Correction
- Less Than 1 Error in 10¹⁴ Bits Read
- MTBF 4,000,000 Hours



ENVIRONMENTAL & POWER

Operating Temperature Range

Standard 0°C to 70°C

Extended -45°C to +90°C



POWER CONSUMPTION

	5.0V
Read	220mA
Write	180mA
Sleep	0.5mA



SHOCK & VIBRATION

Shock	3,000G
Vibration	30G peak-to-peak

CACTUS TECHNOLOGIES

CompactFlash® Memory Card (CF) 303 Pro Series



INDUSTRIAL GRADE COMPACTFLASH PRO SERIES

→ INTERFACE	PC Card ATA and True IDE Mode	
→ INTERFACE TRANSFER RATE	66MB/sec	
→ POWER REQUIREMENT	DC Input Voltage	3V or 5V ± 10%
	Sleep	0.5mA
	Read	220mA
	Write	180mA
→ ENVIRONMENTAL SPECIFICATION	Standard Temperature	0°C to 70°C
	Extended Temperature	-45°C to +90°C
	Humidity	8-95%, non-condensing
	Acoustic Noise	0dB
	Vibration	30G peak to peak max.
	Shock	3000G max.
	Altitude	100,000 feet max.
→ RELIABILITY AND MAINTENANCE	Endurance	2,000,000 erase cycles per block
	MTBF	4,000,000 Hours
	Data Reliability	less than 1 Error in 10 ¹⁴ bits read
→ CARD CAPACITY	128MB to 32GB	

Cactus Technologies Limited

Suite C, 15/F, Capital Trade Center
62 Tsun Yip Street, Kwun Tong
Kowloon, Hong Kong
Tel: +852-2797-2277
Email: sales@cactus-tech.com

Cactus USA

3112 Windsor Road
Suite A356
Austin, Texas 78703
Tel: (512) 775-0746
Email: americas@cactus-tech.com



www.cactus-tech.com