

# IPC-940

## 4U Entry level Rackmount Chassis with Front-Accessible Fan



### Features



- Supports ATX/uATX motherboard
- Shock-resistant disk drive bay design holds up to three 5.25" and one 3.5" disk drives
- Special hold-down clamp design with rubber cushions protects the cards from shocks and vibrations
- Power and HDD activity notification improves system availability
- Front-accessible air filter for easy system maintenance
- Lockable front door prevents unauthorized access

CE FCC

### Specifications


Drive Bay	3.5"	External	1
	5.25"		3
Cooling	Fan		1 (12 cm / 85 CFM)
	Air Filter		Yes
Miscellaneous	LED Indicators		Power and HDD activity
	Control		Power switch and system reset button
	Rear Panel		Motherboard version: Five 9-pin D-Sub & one 25-pin D-sub openings
Environment	Temperature	Operating	0 ~ 40 °C (32 ~ 104 °F)
		Non-Operating	-20 ~ 60 °C (-4 ~ 140 °F)
	Humidity		10 ~ 85 % @ 40 °C, non-condensing
			10 ~ 95 % @ 40 °C, non-condensing
	Vibration (5 ~ 500 Hz)		1 Grms
Physical Characteristics	Shock		2 G
	Dimensions (W x H x D)		10 G (with 11 ms duration, 1/2 sine wave)
	Weight		482 x 177 x 479 mm (19" x 7" x 18.9")
			14.5 kg (31.9 lb) / 14.2 kg (31.2 lb)

### Front View



## Dimensions

Unit: mm [inch]



## Ordering Information

Part Number	Power Supply	Wattage	Switch type
IPC-940MB-25Z	PS8-250ATX-ZE	250W	ATX

## Spare Parts

Part Number	Description
2130006149S000	Fan filter 127 x 127 x 5 mm
2130004802S000	Door filter 142 x 97 x 5 mm

## Optional Accessories

Part Number	Description
IPC-DT-5230E	Mobile rack for converting dual 5.25" drive bays to three 3.5" SATA HDD trays