

# S060316G031

Slim Fit indoor cooling unit

nVent

HOFFMAN

CONNECT AND PROTECT



**Slim Fit air conditioners are specially designed and developed to meet the requirements of industrial customers. Slim Fit air conditioners are easy to specify and ready to use. Available with a cooling capacity range from 300W to 4000W. All units are tested for IP54 for an operating temperature range 10°C to 55°C.**



IP54

H	550.0
W	280
D	140
Cooling capacity L35L35 (W)	370/420
Cooling capacity L35L50 (W)	190/230
Power supply (V/ph/Hz)	115 / 1 / 50-60
Max power consumption L35/L35 ( W at 50/60Hz)	270/300
Max. Nominal current (A)	4.0/3.8
Starting current (A)	13/13
Noise level (dB)	68
Weight (kg)	13
Item no.	S060316G031

**Description:** The Slim Fit indoor air conditioner has extensive features and options. The units have an attractive design that also help optimize the air flow. The units are delivered with a smart controller. The standard unit has three mounting options: Surface, partial recess and fully recess mount, that are easy to change. The air conditioners are available for a cooling range from 300 W to 4000 W. All units are equipped with active condensate management with a heater strip. The factory thermostat setting is 35 °C.

**Type of connection:** Terminal block.

**Material:** Galvanized steel powder coated. Aesthetic designed plastic cover to optimize air flow.

**Temperature limits inside:** +20 °C... + 55 °C

**Temperature limits outside:** +10 °C... + 55 °C

**Protection:** IP54 | TYPE 12

**Finish:** Powder Coat Semi-textured RAL 7035 Light Grey Standard.