

# S101026G031

Slim Fit indoor cooling unit

nVent

HOFFMAN

CONNECT AND PROTECT



**Slim Fit air conditioners are specially designed and developed to meet the requirements of industrial customers. Slim Fit air conditioners are easy to specify and ready to use. Available with a cooling capacity range from 300W to 4000W. All units are tested for IP54 for an operating temperature range 10°C to 55°C.**



IP54

|   |                 |
|---|-----------------|
| H   | 950.0           |
| W   | 400             |
| D   | 259             |
| Cooling capacity L35L35 (W)                   | 1300/1380       |
| Cooling capacity L35L50 (W)                   | 900/1000        |
| Max power consumption L35/L35 ( W at 50/60Hz) | 670/800         |
| Power supply (V/ ph/Hz)                       | 230 / 1 / 50-60 |
| Max. Nominal current (A)                      | 4,1/5,5         |
| Starting current (A)                          | 14/18           |
| Noise level (dB)                              | 71              |
| Weight (kg)                                   | 39              |
| Item no.                                      | S101026G031     |

**Description:** The Slim Fit indoor air conditioner has extensive features and options. The units have an attractive design that also help optimize the air flow. The units are delivered with a smart controller. The standard unit has three mounting options: Surface, partial recess and fully recess mount, that are easy to change. The air conditioners are available for a cooling range from 300 W to 4000 W. All units are equipped with active condensate management with a heater strip. The factory thermostat setting is 35 °C.

**Type of connection:** Terminal block.

**Material:** Galvanized steel powder coated. Aesthetic designed plastic cover to optimize air flow.

**Temperature limits inside:** +20 °C... + 55 °C

**Temperature limits outside:** +10 °C... + 55 °C

**Protection:** IP54 | TYPE 12

**Finish:** Powder Coat Semi-textured RAL 7035 Light Grey Standard.