

# S101046G031

Slim Fit indoor cooling unit

nVent

HOFFMAN

CONNECT AND PROTECT



**Slim Fit air conditioners are specially designed and developed to meet the requirements of industrial customers. Slim Fit air conditioners are easy to specify and ready to use. Available with a cooling capacity range from 300W to 4000W. All units are tested for IP54 for an operating temperature range 10°C to 55°C.**



IP54

H	950.0
W	400
D	259
Cooling capacity L35L35 (W)	1300/1380
Cooling capacity L35L50 (W)	900/1000
Max power consumption L35/L35 ( W at 50/60Hz)	750/960
Power supply (V/ ph/Hz)	400 / 1 / 50... 460 / 1 / 60
Max. Nominal current (A)	2,1/2,4
Starting current (A)	7/8
Noise level (dB)	71
Weight (kg)	45
Item no.	S101046G031

**Description:** The Slim Fit indoor air conditioner has extensive features and options. The units have an attractive design that also help optimize the air flow. The units are delivered with a smart controller. The standard unit has three mounting options: Surface, partial recess and fully recess mount, that are easy to change. The air conditioners are available for a cooling range from 300 W to 4000 W. All units are equipped with active condensate management with a heater strip. The factory thermostat setting is 35 °C.

**Type of connection:** Terminal block.

**Material:** Galvanized steel powder coated. Aesthetic designed plastic cover to optimize air flow.

**Temperature limits inside:** +20 °C... + 55 °C

**Temperature limits outside:** +10 °C... + 55 °C

**Protection:** IP54 | TYPE 12

**Finish:** Powder Coat Semi-textured RAL 7035 Light Grey Standard.