

## **CONNECT AND PROTECT**



Slim Fit air conditioners are specially designed and developed to meet the requirements of industrial customers. Slim Fit air conditioners are easy to specify and ready to use. Available with a cooling capacity range from 300W to 4000W. All units are tested for IP54 for an operating temperature range 10°C to 55°C.



IP54

| Н  | 950.0                     |
|--|---------------------------|
| W  | 400                       |
| D  | 259                       |
| Cooling capacity<br>L35L35 (W)                         | 1800/1880                 |
| Cooling capacity<br>L35L50 (W)                         | 1300/1380                 |
| Max power<br>consumption<br>L35/L35 ( W at<br>50/60Hz) | 930/1130                  |
| Power supply (V/<br>ph/Hz)                             | 400 / 3 / 50 460 / 3 / 60 |
| Max. Nominal<br>current (A)                            | 2,1/2,4                   |
| Starting current (A)                                   | 7/8                       |
| Noise level (dB)                                       | 73                        |
| Weight (kg)  | 43                        |
| Item no.   | S101546G031               |
|  |                           |

**Description:** The Slim Fit indoor air conditioner has extensive features and options. The units have an attractive design that also help optimize the air flow. The units are delivered with a smart controller. The standard unit has three mounting options: Surface, partial recess and fully recess mount, that are easy to change. The air conditioners are available for a cooling range from 300 W to 4000 W. All units are equipped with active condensate management with a heater strip. The factory thermostat setting is 35 °C.

Type of connection: Terminal block.

**Material:** Galvanized steel powder coated. Aesthetic designed plastic cover to optimize air flow.

Temperature limits inside: +20 °C... + 55 °C
Temperature limits outside: +10 °C... + 55 °C

**Protection:** IP54 | TYPE 12

Finish: Powder Coat Semi-textured RAL 7035 Light Grey Standard.