

Datasheet | Rev. 2.0 | 2021

IMM2G72D3(L)RVD4AG (Die Revision D) 16GByte (2G x 72 Bit)

16GB DDR3 VLP Registered DIMM
RoHS Compliant Product

Remark:

Please refer to the last page of the i) Contents ii) List of Table iii) List of Figures.

We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all? Your feedback will help us to continuously improve the quality of this document. Please send your proposal (including a reference to this document) to: sales@intelligentmemory.com

Features

- 240-Pin Registered Dual-In-Line Memory Module
- Capacity: 16GB
- JEDEC-Standard
- Bi-directional Differential Data-Strobe
- 72 Bit Data Bus Width with ECC
- Programmable CAS Latency (CL):
 - PC3-12800: 5, 6, 7, 8, 9, 10, 11
 - PC3-10600: 5, 6, 7, 8, 9, 10
- Programmable CAS Write Latency (CWL):
 - PC3-12800: 5, 6, 7, 8
 - PC3-10600: 5, 6, 7
- Programmable Additive Latency (Posted /CAS): 0, CL-2 or CL-1(Clock)
- On-Die Termination (ODT)
- ZQ Calibration Supported
- Burst Type (Sequential & Interleave)
- Burst Length: 4, 8
- Refresh Mode: Auto and Self
- 8192 Refresh Cycles / 64ms
- Asynchronous Reset
- On-board I2C Temperature Sensor with Integrated Serial Presence Detect (SPD) EEPROM
- Gold Edge Contacts
- 100% RoHS-Compliant
- Very Low Profile Module Height: 18.75mm (0.74inch)

Table 1 – Ordering Information for RoHS Compliant Product

Part Number	Module Density	Configuration	# of Ranks	Module Type
IMM2G72D3xRVD4AG-Dzzzy	16GB	2Gx72	2	16GB DDR3 VLP Registered DIMM

Notes:

- x: Operating Voltage
- y: Operating Temperature
- zzz: Speed Grade

Table 2 – Operating Voltage

Part Number	Operating Voltage
Blank	$V_{DD}, V_{DDQ} = 1.5V (1.425V-1.575V)$
L	$V_{DD}, V_{DDQ} = 1.35V (1.283V-1.45V)$ Backward compatible to $V_{DD}, V_{DDQ} = 1.5V (1.425V-1.575V)$

Table 3 – Temperature Grade

Part Number	Temperature Grade	Tcase
Blank	Commercial temperature	0°C to 95°C
I	Industrial temperature	-40°C to 95°C

Remark: Tcase is the case surface temperature on the center/top side of the DRAM. The refresh rate is required to double when $85^{\circ}C < T_{case} \leq 95^{\circ}C$.

Table 4 – Speed Grade

Part Number	Speed Grade	Max Clock Frequency (min. Clock Cycle time @ min. CAS Latency)
125	PC3-12800 (DDR3-1600)	800MHz (1.25ns@CL=11)
15E	PC3-10600 (DDR3-1333)	667MHz (1.5ns@CL=9)

Table 5 – Memory Chip Information

Part Number	Base Device Brand	Base Device	Voltage	Type	Chip Packing
IMM2G72D3(L)RVD4AG-Dzzzy	I'M	IM8G04D3FDDG	1.35V/1.5V	1Gx4x2 DDP	Lead Free

Part Number Decoder




Table 6 – Addressing

Parameter	16GB
Refresh count	8K
Row address	64K A[15:0]
Device bank address	8 BA[2:0]
Device configuration	8Gb (1Gx4x2 DDP)
Column address	2K A[9:0], A11
Module rank address	2 /S[1:0]
Number of devices	18

Table 7 – Pin Assignment

Pin	Name	Pin	Name	Pin	Name	Pin	Name
1	V _{REFDQ}	121	V _{SS}	61	A2	181	A1
2	V _{SS}	122	D4	62	V _{DD}	182	V _{DD}
3	D0	123	D5	63	CK1	183	V _{DD}
4	D1	124	V _{SS}	64	/CK1	184	CK0
5	V _{SS}	125	DQS9	65	V _{DD}	185	/CK0
6	/DQS0	126	/DQS9	66	V _{DD}	186	V _{DD}
7	DQS0	127	V _{SS}	67	V _{REFCA}	187	/EVENT
8	V _{SS}	128	D6	68	PAR_IN	188	A0
9	D2	129	D7	69	V _{DD}	189	V _{DD}
10	D3	130	V _{SS}	70	A10, AP	190	BA1
11	V _{SS}	131	D12	71	BA0	191	V _{DD}
12	D8	132	D13	72	V _{DD}	192	/RAS
13	D9	133	V _{SS}	73	/WE	193	/S0
14	V _{SS}	134	DQS10	74	/CAS	194	V _{DD}
15	/DQS1	135	/DQS10	75	V _{DD}	195	ODT0
16	DQS1	136	V _{SS}	76	/S1	196	A13
17	V _{SS}	137	D14	77	ODT1	197	V _{DD}
18	D10	138	D15	78	V _{DD}	198	NC
19	D11	139	V _{SS}	79	NC	199	V _{SS}
20	V _{SS}	140	D20	80	V _{SS}	200	D36
21	D16	141	D21	81	D32	201	D37
22	D17	142	V _{SS}	82	D33	202	V _{SS}
23	V _{SS}	143	DQS11	83	V _{SS}	203	DQS13
24	/DQS2	144	/DQS11	84	/DQS4	204	/DQS13
25	DQS2	145	V _{SS}	85	DQS4	205	V _{SS}
26	V _{SS}	146	D22	86	V _{SS}	206	D38
27	D18	147	D23	87	D34	207	D39
28	D19	148	V _{SS}	88	D35	208	V _{SS}
29	V _{SS}	149	D28	89	V _{SS}	209	D44
30	D24	150	D29	90	D40	210	D45
31	D25	151	V _{SS}	91	D41	211	V _{SS}
32	V _{SS}	152	DQS12	92	V _{SS}	212	DQS14
33	/DQS3	153	/DQS12	93	/DQS5	213	/DQS14
34	DQS3	154	V _{SS}	94	DQS5	214	V _{SS}
35	V _{SS}	155	D30	95	V _{SS}	215	D46
36	D26	156	D31	96	D42	216	D47
37	D27	157	V _{SS}	97	D43	217	V _{SS}
38	V _{SS}	158	CB4	98	V _{SS}	218	D52
39	CB0	159	CB5	99	D48	219	D53
40	CB1	160	V _{SS}	100	D49	220	V _{SS}
41	V _{SS}	161	DQS17	101	V _{SS}	221	DQS15
42	/DQS8	162	/DQS17	102	/DQS6	222	/DQS15
43	DQS8	163	V _{SS}	103	DQS6	223	V _{SS}
44	V _{SS}	164	CB6	104	V _{SS}	224	D54
45	CB2	165	CB7	105	D50	225	D55
46	CB3	166	V _{SS}	106	D51	226	V _{SS}
47	V _{SS}	167	NC	107	V _{SS}	227	D60
48	V _{TT}	168	/RESET	108	D56	228	D61
49	V _{TT}	169	CKE1	109	D57	229	V _{SS}
50	CKE0	170	V _{DD}	110	V _{SS}	230	DQS16
51	V _{DD}	171	A15	111	/DQS7	231	/DQS16
52	BA2	172	A14	112	DQS7	232	V _{SS}
53	/ERR_OUT	173	V _{DD}	113	V _{SS}	233	D62
54	V _{DD}	174	A12, /BC	114	D58	234	D63
55	A11	175	A9	115	D59	235	V _{SS}
56	A7	176	V _{DD}	116	V _{SS}	236	V _{DDSPD}
57	V _{DD}	177	A8	117	SA0	237	SA1
58	A5	178	A6	118	SCL	238	SDA
59	A4	179	V _{DD}	119	SA2	239	V _{SS}
60	V _{DD}	180	A3	120	V _{TT}	240	V _{TT}

Table 8 – Pin Description

Pin Name	Description	Pin Name	Description
V _{DD}	SDRAM core power supply	V _{REFDQ}	SDRAM I/O reference supply
V _{REFCA}	SDRAM command/address reference supply	V _{SS}	Power supply return (ground)
A0-A15	SDRAM address bus	BA0-BA2	SDRAM bank addresses
CK0, CK1	SDRAM clocks (positive line of differential pair)	/CK0, /CK1	SDRAM clocks (negative line of differential pair)
/RAS	SDRAM row address strobe	/CAS	SDRAM column address strobe
/WE	SDRAM write enable	CKE0-CKE1	SDRAM clock enable lines
/S0-/S1	DIMM rank select lines	ODT0-ODT1	On-die termination control lines
DQS0-DQS17	SDRAM data strobes (positive line of differential pair)	/DQS0- /DQS17	SDRAM data strobes (negative line of differential pair)
D0-D63	DIMM memory data bus	CB0-CB7	Data check bits input/output
SCL	EEPROM clock	SDA	EEPROM data line
SA0-SA2	EEPROM address input	V _{DDSPD}	EEPROM positive power supply
PAR_IN	Parity input	/EVENT	Temperature event
/ERR_OUT	Parity error output	/RESET	Register and SDRAM control pin
V _{TT}	Termination voltage	NC	Spare pins (no connect)

Module Dimension

Figure 1 – 240 Pin DDR3 SDRAM VLP Registered DIMM




Table 9 – PCB Dimension

Symbol	MIN	NOM	MAX
A	18.60	18.75	18.90
A1	9.35	9.50	9.65
A2	0.05	0.20	0.35
A3	15.65	15.80	15.95
D	133.20	133.35	133.50
D1	12.00 Basic		
D2	2.50 Basic		
e1	47.00 Basic		
e2	71.00 Basic		
E1			4.00

Notes:

- All dimensioning and tolerancing conform to ASME Y14.5M-1994.
- Tolerances for all dimensions ±0.15 unless otherwise specified.
- All dimensions are in millimeters.

Figure 2 – Functional Block Diagram (Page 1 of 4)




Figure 3 – Functional Block Diagram (Page 2 of 4)




Figure 4 – Functional Block Diagram (Page 3 of 4)





Figure 5 – Functional Block Diagram (Page 4 of 4)



Electrical Parameter

Table 10 – Absolute Maximum DC Ratings

Parameter	Symbol	Rating	Units	Notes
Voltage on V_{DD} , pin relative to V_{SS}	V_{DD}	-0.4 ~ 1.975	V	1,3
Voltage on V_{DDQ} , pin relative to V_{SS}	V_{DDQ}	-0.4 ~ 1.975	V	1,3
Voltage on any pins relative to V_{SS}	V_{IN}, V_{OUT}	-0.4 ~ 1.975	V	1
DRAM Storage temperature	T_{STG}	-55 ~ 150	°C	1,2
DRAM Operation temperature for Commercial temperature product	T_{case}	0 ~ 95	°C	2,4,5
DRAM Operation temperature for Industrial temperature product	T_{case}	-40 ~ 95	°C	2,4,5

Notes:

- Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.
- Storage Temperature or DRAM operation temperature is the case surface temperature on the center/top side of the DRAM. For the measurement conditions, please refer to JESD51-2 standard.
- V_{DD} and V_{DDQ} must be within 300mV of each other at all times; and V_{REF} must not be greater than $0.6 \times V_{DDQ}$, when V_{DD} and V_{DDQ} are less than 500mV; V_{REF} may be equal to or less than 300mV.
- The Normal Temperature Range specifies the temperatures when all DRAM specifications will be supported. During operation, the DRAM case temperature must be maintained between 0-85 °C under all operating conditions.
- Some applications require operation of the Extended Temperature Range between 85 °C and 95 °C case temperature. Full Specifications are guaranteed in this range but the following additional conditions apply a) Refresh commands must be doubled in frequency, therefore reducing the refresh interval t_{REFI} to 3.9us. b) If Self-Refresh operation is required in the Extended Temperature Range, then it is mandatory to either use the Manual Self-Refresh mode with Extended Temperature Range capability (MR2 A6 = 0b and MR2 A7 = 1b) or enable the optional Auto Self-Refresh mode (MR2 A6 = 1b and MR2 A7 = 0b).

Table 11 – DC Electrical Characteristics and Operating Conditions

Parameter / Condition	Symbol	Rating			Units	Notes
		Min	Typ	Max		
Supply voltage	V_{DD}	1.283	1.35	1.45	V	1,2
I/O supply voltage	V_{DDQ}				V	1,2
Supply voltage	V_{DD}	1.425	1.5	1.575	V	1,2,3
I/O supply voltage	V_{DDQ}				V	1,2,3

Notes:

- V_{DD} and V_{DDQ} must track one another. V_{DDQ} must be less than or equal to V_{DD} . $V_{SS} = V_{SSQ}$.
- V_{DD} and V_{DDQ} may include AC noise of +/-50mV (250 kHz to 20 MHz) in addition to the DC (0 Hz to 250 kHz) specifications. V_{DD} and V_{DDQ} must be at same level for valid AC timing parameters.
- Module is backward-compatible with 1.5V operation.

Table 12 – DC Electrical Characteristics and Input Conditions

Parameter / Condition	Symbol	Rating			Units	Notes
		Min	Typ	Max		
Input reference voltage; command/address bus	$V_{REFCA(DC)}$	$0.49 * V_{DD}$	$0.50 * V_{DD}$	$0.51 * V_{DD}$	V	1,2
I/O reference voltage DQ bus	$V_{REFDQ(DC)}$	$0.49 * V_{DD}$	$0.50 * V_{DD}$	$0.51 * V_{DD}$	V	2,3
Command/address termination voltage (system level, not direct DRAM input)	V_{TT}	-	$0.50 * V_{DDQ}$	-	V	4

Notes:

- $V_{REFCA(DC)}$ is expected to be approximately $0.5 \times V_{DD}$ and to track variations in the DC level. Externally generated peak noise (noncommon mode) on V_{REFCA} may not exceed $\pm 1\% \times V_{DD}$ around the $V_{REFCA(DC)}$ value. Peak-to-peak AC noise on V_{REFCA} should not exceed $\pm 2\%$ of $V_{REFCA(DC)}$.
- DC values are determined to be less than 20 MHz in frequency. DRAM must meet specifications if the DRAM induces additional AC noise greater than 20 MHz in frequency.
- $V_{REFDQ(DC)}$ is expected to be approximately $0.5 \times V_{DD}$ and to track variations in the DC level. Externally generated peak noise (noncommon mode) on V_{REFDQ} may not exceed $\pm 1\% \times V_{DD}$ around the $V_{REFDQ(DC)}$ value. Peak-to-peak AC noise on V_{REFDQ} should not exceed $\pm 2\%$ of $V_{REFDQ(DC)}$.
- V_{TT} is not applied directly to the device. V_{TT} is a system supply for signal termination resistors. MIN and MAX values are system-dependent.

Table 13 – Input Switching Conditions

Parameter / Condition	Symbol	Value		Units	
		1.35V	1.5V		
Command and Address					
Input high AC voltage: Logic 1 @ 175mV	DDR3-1600, 1333	$V_{IH(AC175)min}$	-	175	mV
Input high AC voltage: Logic 1 @ 160mV	DDR3-1600, 1333	$V_{IH(AC160)min}$	160	-	mV
Input high AC voltage: Logic 1 @ 150mV	DDR3-1600, 1333	$V_{IH(AC150)min}$	-	150	mV
Input high AC voltage: Logic 1 @ 135mV	DDR3-1600, 1333	$V_{IH(AC135)min}$	135	-	mV
Input high DC voltage: Logic 1 @ 100mV	DDR3-1600, 1333	$V_{IH(DC100)min}$	-	100	mV
Input high DC voltage: Logic 1 @ 90mV	DDR3-1600, 1333	$V_{IH(DC90)min}$	90	-	mV
Input low DC voltage: Logic 0 @ -90mV	DDR3-1600, 1333	$V_{IL(DC90)max}$	-90	-	mV
Input low DC voltage: Logic 0 @ -100mV	DDR3-1600, 1333	$V_{IL(DC100)max}$	-	-100	mV
Input low AC voltage: Logic 0 @ -135mV	DDR3-1600, 1333	$V_{IL(AC135)max}$	-135	-	
Input low AC voltage: Logic 0 @ -150mV	DDR3-1600, 1333	$V_{IL(AC150)max}$	-	-150	mV
Input low AC voltage: Logic 0 @ -160mV	DDR3-1600, 1333	$V_{IL(AC160)max}$	-160	-	mV
Input low AC voltage: Logic 0 @ -175mV	DDR3-1600, 1333	$V_{IL(AC175)max}$	-	-175	mV

Parameter / Condition	Symbol	Value		Units	
		1.35V	1.5V		
DQ and DM					
Input high AC voltage: Logic 1	DDR3-1600, 1333	$V_{IH(AC150)min}$	-	150	mV
Input high AC voltage: Logic 1	DDR3-1600, 1333	$V_{IH(AC135)min}$	135	-	mV
Input high DC voltage: Logic 1	DDR3-1600, 1333	$V_{IH(DC100)min}$	-	100	mV
Input high DC voltage: Logic 1	DDR3-1600, 1333	$V_{IH(DC90)min}$	90	-	mV
Input low DC voltage: Logic 0	DDR3-1600, 1333	$V_{IL(DC90)max}$	-90	-	mV
Input low DC voltage: Logic 0	DDR3-1600, 1333	$V_{IL(DC100)max}$	-	-100	mV
Input low AC voltage: Logic 0	DDR3-1600, 1333	$V_{IL(AC135)max}$	-135	-	mV
Input low AC voltage: Logic 0	DDR3-1600, 1333	$V_{IL(AC150)max}$	-	-150	mV

Notes:

1. All voltages are referenced to V_{REF} . V_{REF} is V_{REFCA} for control, command, and address. All slew rates and setup/hold times are specified at the DRAM ball. V_{REF} is V_{REFDQ} for DQ and DM inputs.
2. Input setup timing parameters (t_{IS} and t_{DS}) are referenced at $V_{IL(AC)}/V_{IH(AC)}$, not $V_{REF(DC)}$.
3. Input hold timing parameters (t_{IH} and t_{DH}) are referenced at $V_{IL(DC)}/V_{IH(DC)}$, not $V_{REF(DC)}$.
4. Single-ended input slew rate = 1 V/ns; maximum input voltage swing under test is 900mV (peak-to-peak).

Table 14 – Differential Input Operating Conditions (CK, /CK and DQS, /DQS)

Parameter / Condition	Symbol	Rating		Units	Notes
		Min	Max		
Differential input voltage logic high – slew (1.35V)	$V_{IH,diff}$	+180	-	mV	1
Differential input voltage logic high – slew (1.5V)	$V_{IH,diff}$	+200	-	mV	1
Differential input voltage logic low – slew (1.35V)	$V_{IL,diff}$	-	-180	mV	1
Differential input voltage logic low – slew (1.5V)	$V_{IL,diff}$	-	-200	mV	1
Differential input voltage logic high	$V_{IH,diff(AC)}$	$2 * (V_{IH(AC)} - V_{REF})$	-	mV	2
Differential input voltage logic low	$V_{IL,diff(AC)}$	-	$2 * (V_{IL(AC)} - V_{REF})$	mV	3
Differential Input Cross Point Voltage relative to VDD/2 for CK, /CK (1.35V Operation)	V_{IX}	-150	150	mV	4
Differential Input Cross Point Voltage relative to VDD/2 for CK, /CK (1.5V Operation)	V_{IX}	-150	150	mV	4
		-175	175		5
Differential Input Cross Point Voltage relative to VDD/2 for DQS, /DQS (1.35V Operation)	V_{IX}	-150	150	mV	4
Differential Input Cross Point Voltage relative to VDD/2 for DQS, /DQS (1.5V Operation)	V_{IX}	-150	150	mV	4

Notes:

1. Defines slew rate reference points, relative to input crossing voltages.
2. Minimum DC limit is relative to single-ended signals; overshoot specifications are applicable.
3. Maximum DC limit is relative to single-ended signals; undershoot specifications are applicable.
4. The relation between V_{IX} Min/Max and V_{SEL}/V_{SEH} should satisfy following:
 $(V_{DD}/2) + V_{IX(min)} - V_{SEL} \geq 25mV$;
 $V_{SEH} - ((V_{DD}/2) + V_{IX(max)}) \geq 25mV$;
5. Extended range for V_{IX} is only allowed for clock and if single-ended clock input signals CK and /CK are monotonic with a single-ended swing V_{SEL}/V_{SEH} of at least $V_{DD}/2 \pm 250mV$, and when the differential slew rate of CK-/CK is larger than 3V/ns.

Table 15 – Single-Ended Output Driver Characteristics

Parameter / Condition	Symbol	Rating		Units	Notes
		Min	Max		
Output slew rate: Single-ended; For rising and falling edges, measure between $V_{OL(AC)} = V_{TT} - 0.1 * V_{DDQ}$ and $V_{OH(AC)} = V_{TT} + 0.1 * V_{DDQ}$ (1.35V)	SRQ _{se}	1.75	5	V/ns	1,2,3
Output slew rate: Single-ended; For rising and falling edges, measure between $V_{OL(AC)} = V_{TT} - 0.1 * V_{DDQ}$ and $V_{OH(AC)} = V_{TT} + 0.1 * V_{DDQ}$ (1.5V)	SRQ _{se}	2.5	5	V/ns	1,2,3
Single-ended high level for strobes	V _{SEH}	$V_{DDQ}/2 + 175$	-	mV	2
Single-ended high level for CK, /CK		$V_{DD}/2 + 175$	-	mV	2
Single-ended low level for strobes	V _{SEL}	-	$V_{DDQ}/2 - 175$	mV	3
Single-ended low level for CK, /CK		-	$V_{DD}/2 - 175$	mV	3
Single-ended DC high-level output voltage	V _{OH(DC)}	$0.8 * V_{DDQ}$		V	1,2
Single-ended DC mid-level output voltage	V _{OM(DC)}	$0.5 * V_{DDQ}$		V	1,2
Single-ended DC low-level output voltage	V _{OL(DC)}	$0.2 * V_{DDQ}$		V	1,2
Single-ended AC high-level output voltage	V _{OH(AC)}	$V_{TT} + 0.1 * V_{DDQ}$		V	1,2
Single-ended AC low-level output voltage	V _{OL(AC)}	$V_{TT} - 0.1 * V_{DDQ}$		V	1,2
Test load for AC timing and output slew rates	Output to V _{TT} (V _{DDQ} /2) via 25Ω resistor				

Notes:

1. RZQ of 240Ω (±1%) with RZQ/7 enabled (default 34Ω driver) and is applicable after proper ZQ calibration has been performed at a stable temperature and voltage (V_{DDQ} = V_{DD}, V_{SSQ} = V_{SS}).
2. V_{TT} = V_{DDQ}/2.
3. The 6 V/ns maximum is applicable for a single DQ signal when it is switching either from HIGH to LOW or LOW to HIGH while the remaining DQ signals in the same byte lane are either all static or all switching the opposite direction. For all other DQ signal switching combinations, the maximum limit of 6 V/ns is reduced to 5 V/ns.

Table 16 – Differential Output Driver Characteristics

Parameter / Condition	Symbol	Rating		Units	Notes
		Min	Max		
Output slew rate: Differential; For rising and falling edges, measure between $V_{OL,diff(AC)} = -0.2 * V_{DDQ}$ and $V_{OH,diff(AC)} = +0.2 * V_{DDQ}$ (1.35V)	SRQ _{diff}	3.5	12	V/ns	1
Output slew rate: Differential; For rising and falling edges, measure between $V_{OL,diff(AC)} = -0.2 * V_{DDQ}$ and $V_{OH,diff(AC)} = +0.2 * V_{DDQ}$ (1.5V)	SRQ _{diff}	5	10	V/ns	1
Differential high-level output voltage	V _{OH,diff(AC)}	$+0.2 * V_{DDQ}$		V	1
Differential low-level output voltage	V _{OL,diff(AC)}	$-0.2 * V_{DDQ}$		V	1
Test load for AC timing and output slew rates	Output to V _{TT} (V _{DDQ} /2) via 25Ω resistor				

Notes:

1. RZQ of 240Ω (±1%) with RZQ/7 enabled (default 34Ω driver) and is applicable after proper ZQ calibration has been performed at a stable temperature and voltage (V_{DDQ} = V_{DD}, V_{SSQ} = V_{SS}).
2. V_{REF} = V_{DDQ}/2; slew rate @ 5V/ns, interpolate for faster slew rate.

For part number IMM2G72D3(L)RVD4AG-D125(I)

Table 17 – I_{DD} Specifications with Conditions and Operation Current

Parameter / Condition	Symbol	Current	Units	Notes
Operating current 0; One bank ACTIVATE-to-PRECHARGE	I _{DD0}	1098	mA	1, 2
Operating current 1; One bank ACTIVATE-to-READ-to-PRECHARGE	I _{DD1}	1242	mA	1, 2
Precharge power-down current; Slow exit	I _{DD2P0}	288	mA	1, 2
Precharge power-down current; Fast exit	I _{DD2P1}	396	mA	1, 2
Precharge quiet standby current	I _{DD2Q}	576	mA	1, 2
Precharge standby current	I _{DD2N}	576	mA	1, 2
Precharge standby ODT current	I _{DD2NT}	648	mA	1, 2
Active power-down current	I _{DD3P}	612	mA	1, 2
Active standby current	I _{DD3N}	684	mA	1, 2
Burst read operating current	I _{DD4R}	1818	mA	1, 2
Burst write operating current	I _{DD4W}	1854	mA	1, 2
Refresh current	I _{DD5B}	4374	mA	1, 2
Self refresh temperature current: MAX T _{case} = 85°C	I _{DD6}	360	mA	1, 2
Self refresh temperature current (SRT-enabled): MAX T _{case} = 95°C	I _{DD6ET}	432	mA	1, 2
All banks interleaved read current	I _{DD7}	2484	mA	1, 2
Reset current	I _{DD8}	360	mA	1, 2

Notes:

1. Value shown for DDR3 SDRAM only and are computed from values specified in the 8Gbit component data sheet.
2. All ranks in this I_{DD} conditions.

For part number IMM2G72D3(L)RVD4AG-D125(I)

Table 18 – AC Timing Parameter and Operating Conditions

Parameter / Condition		Symbol	Min	Max	Units
Clock Timing					
Minimum Clock Cycle Time (DLL off mode)		$t_{CK}(DLL_OFF)$	8	-	ns
Clock periods average: DLL enable mode (CL = 11, CWL = 8)		$t_{CK}(avg)$	1.25	<1.5	ns
High pulse width average		$t_{CH}(avg)$	0.47	0.53	$t_{CK}(avg)$
Low pulse width average		$t_{CL}(avg)$	0.47	0.53	$t_{CK}(avg)$
Clock period jitter	DLL locked	t_{JITper}	-70	70	ps
	DLL locking	$t_{JIT(per,lock)}$	-60	60	ps
Clock absolute period		$t_{CK}(abs)$	$t_{CK}(avg) Min + t_{JITper} Min$	$t_{CK}(avg) Max + t_{JITper} Max$	ps
Clock absolute high pulse width		$t_{CH}(abs)$	0.43	-	$t_{CK}(avg)$
Clock absolute low pulse width		$t_{CL}(abs)$	0.43	-	$t_{CK}(avg)$
Cycle-to-cycle jitter	DLL locked	t_{JITcc}	140		ps
	DLL locking	$t_{JIT(cc,lock)}$	120		ps
Cumulative error across	2 cycles	$t_{ERR(2per)}$	-103	103	ps
	3 cycles	$t_{ERR(3per)}$	-122	122	ps
	4 cycles	$t_{ERR(4per)}$	-136	136	ps
	5 cycles	$t_{ERR(5per)}$	-147	147	ps
	6 cycles	$t_{ERR(6per)}$	-155	155	ps
	7 cycles	$t_{ERR(7per)}$	-163	163	ps
	8 cycles	$t_{ERR(8per)}$	-169	169	ps
	9 cycles	$t_{ERR(9per)}$	-175	175	ps
	10 cycles	$t_{ERR(10per)}$	-180	180	ps
	11 cycles	$t_{ERR(11per)}$	-184	184	ps
	12 cycles	$t_{ERR(12per)}$	-188	188	ps
		n = 14,...49, 50 cycles	$t_{ERR(nper)}$	$(1+0.68ln[n]) * t_{JITper} Min$	$(1+0.68ln[n]) * t_{JITper} Max$
DQ Input Timing					
Data setup time to DQS, /DQS (1.35V)	Base (specification)	$t_{DS}(AC135)$	25	-	ps
Data setup time to DQS, /DQS (1.5V)	Base (specification)	$t_{DS}(AC150)$	10	-	ps
Data hold time from DQS, /DQS (1.35V)	Base (specification)	$t_{DH}(DC90)$	55	-	ps
Data hold time from DQS, /DQS (1.5V)	Base (specification)	$t_{DH}(DC100)$	45	-	ps
Minimum data pulse width		t_{DIPW}	360	-	ps
DQ Output Timing					
DQS, /DQS to DQ skew, per access		t_{DQSQ}	-	100	ps
DQ output hold time from DQS, /DQS		t_{QH}	0.38	-	$t_{CK}(avg)$
DQ Low-Z time from CK, /CK		$t_{LZ}(DQ)$	-450	225	ps
DQ High-Z time from CK, /CK		$t_{HZ}(DQ)$	-	225	ps
DQ Strobe Input Timing					
DQS, /DQS rising to CK, /CK rising		t_{DQSS}	-0.27	0.27	$t_{CK}(avg)$
DQS, /DQS differential input low pulse width		t_{DQSL}	0.45	0.55	$t_{CK}(avg)$
DQS, /DQS falling setup to CK, /CK rising		t_{DSS}	0.18	-	$t_{CK}(avg)$
DQS, /DQS falling hold from CK, /CK rising		t_{DSH}	0.18	-	$t_{CK}(avg)$
DQS, /DQS differential input high pulse width		t_{DQSH}	0.45	0.55	$t_{CK}(avg)$
DQS, /DQS differential WRITE preamble		t_{WPRE}	0.9	-	$t_{CK}(avg)$
DQS, /DQS differential WRITE postamble		t_{WPST}	0.3	-	$t_{CK}(avg)$

For part number IMM2G72D3(L)RVD4AG-D125(I)

Parameter / Condition		Symbol	Min	Max	Units
DQ Strobe Output Timing					
DQS, /DQS rising to/from CK, /CK		t_{DQSK}	-225	225	ps
DQS, /DQS differential output high time		t_{QSH}	0.40	-	$t_{CK}(avg)$
DQS, /DQS differential output low time		t_{QSL}	0.40	-	$t_{CK}(avg)$
DQS, /DQS Low-Z time (RL-1)		$t_{LZ}(DQS)$	-450	225	ps
DQS, /DQS High-Z time (RL+BL/2)		$t_{HZ}(DQS)$	-	225	ps
DQS, /DQS differential READ preamble		t_{RPRE}	0.9	-	$t_{CK}(avg)$
DQS, /DQS differential READ postamble		t_{RPST}	0.3	-	$t_{CK}(avg)$
Command and Address Timing					
DLL locking time		t_{DLLK}	512	-	nCK
CTRL, CMD, ADDR setup to CK, /CK (1.35V)	Base (specification)	$t_{IS}(AC160)$	60	-	ps
	Base (specification)	$t_{IS}(AC135)$	185	-	ps
CTRL, CMD, ADDR setup to CK, /CK (1.5V)	Base (specification)	$t_{IS}(AC175)$	45	-	ps
	Base (specification)	$t_{IS}(AC150)$	170	-	ps
CTRL, CMD, ADDR hold from CK, /CK (1.35V)	Base (specification)	$t_{IH}(DC90)$	130	-	ps
	Base (specification)	$t_{IH}(DC100)$	120	-	ps
Minimum CTRL, CMD, ADDR pulse width		t_{IPW}	560	-	ps
ACTIVATE to internal READ or WRITE delay		t_{RCD}	13.125	-	ns
PRECHARGE command period		t_{RP}	13.125	-	ns
ACTIVATE-to-PRECHARGE command period		t_{RAS}	35	$9 * t_{REFI}$	ns
ACTIVATE-to-ACTIVATE command period		t_{RC}	48.125	-	ns
ACTIVATE-to-ACTIVATE minimum period (1KB page size)		t_{RRD}	greater of 4nCK or 6ns	-	-
ACTIVATE-to-ACTIVATE minimum period (2KB page size)		t_{RRD}	greater of 4nCK or 7.5ns	-	-
Four ACTIVATE windows (1KB page size)		t_{FAW}	30	-	ns
Four ACTIVATE windows (2KB page size)		t_{FAW}	40	-	ns
Write recovery time		t_{WR}	15	-	ns
Delay from start of internal WRITE transaction to internal READ command		t_{WTR}	greater of 4nCK or 7.5ns	-	-
READ-to-PRECHARGE time		t_{RTP}	greater of 4nCK or 7.5ns	-	-
/CAS-to-/CAS command delay		t_{CCD}	4	-	nCK
Auto precharge write recovery + precharge time		t_{DAL}	$WR + t_{RP} / t_{CK}(avg)$	-	t_{CK}
MODE REGISTER SET command cycle time		t_{MRD}	4	-	nCK
MODE REGISTER SET command update delay		t_{MOD}	greater of 12nCK or 15ns	-	-
MULTIPURPOSE REGISTER READ burst end to mode register set for multipurpose register exit		t_{MPRR}	1	-	nCK
Calibration Timing					
ZQCL command: Long calibration time	POWER-UP and RESET operation	t_{zqinit}	greater of 512nCK or 640ns	-	-
	Normal operation	t_{zqoper}	greater of 256nCK or 320ns	-	-
ZQCS command: Short calibration time		t_{zqcs}	greater of 64nCK or 80ns	-	-
Initialization and Reset Timing					
Exit reset from CKE HIGH to valid command		t_{XPR}	greater of 5nCK or $t_{RFC}(min)+10ns$	-	-
Refresh Timing					
REFRESH-to-ACTIVATE or REFRESH command period		t_{RFC}	260	-	ns

For part number IMM2G72D3(L)RVD4AG-D125(I)

Parameter / Condition		Symbol	Min	Max	Units
Maximum refresh period	T _{case} ≤ 85°C	-	64 (1X)		ms
	T _{case} > 85°C		32 (2X)		
Maximum average periodic refresh	T _{case} ≤ 85°C	t _{REFI}	7.8 (64ms/8192)		us
	T _{case} > 85°C		3.9 (32ms/8192)		
Self Refresh Timing					
Exit self refresh to commands not requiring a locked DLL		t _{XS}	greater of 5nCK or t _{RFC} Min+10ns	-	-
Exit self refresh to commands requiring a locked DLL		t _{XS} DLL	t _{DLLK} Min	-	nCK
Minimum CKE low pulse width for self refresh entry to self refresh exit timing		t _{CKESR}	t _{CKE} Min + 1nCK	-	-
Valid clocks after self refresh entry or power down entry		t _{CKSRE}	greater of 5nCK or 10ns	-	-
Valid clocks before self refresh exit, power-down exit, or reset exit		t _{CKSRX}	greater of 5nCK or 10ns	-	-
Power-Down Timing					
CKE MIN pulse width		t _{CKE}	greater of 3nCK or 5ns	-	-
Command pass disable delay		t _{CPDED}	1	-	nCK
Power-down entry to power exit timing		t _{PD}	t _{CKE} Min	9 * t _{REFI}	-
Power-Down Entry Minimum Timing					
ACTIVATE command to power-down entry		t _{ACTPDEN}	1	-	nCK
PRECHARGE/PRECHARGE ALL command to power-down entry		t _{PRPDEN}	1	-	nCK
REFRESH command to power-down entry		t _{REFPDEN}	1	-	nCK
MRS command to power-down entry		t _{MRS} PDEN	t _{MOD} Min	-	-
READ/READ with auto precharge command to power-down entry		t _{RD} PDEN	RL + 4 + 1	-	nCK
WRITE command to power-down entry	BL8 (OTF, MRS) BC4OTF	t _{WR} PDEN	WL + 4 + t _{WR} /t _{CK} (avg)	-	nCK
	BC4MRS	t _{WR} PDEN	WL + 2 + t _{WR} /t _{CK} (avg)	-	nCK
WRITE with auto precharge command to power-down entry	BL8 (OTF, MRS) BC4OTF	t _{WRAP} PDEN	WL + 4 + t _{WR} + 1	-	nCK
	BC4MRS	t _{WRAP} PDEN	WL + 2 + t _{WR} + 1	-	nCK
Power-Down Exit Timing					
DLL on, any valid command, or DLL off to commands not requiring locked DLL		t _{XP}	greater of 3nCK or 6ns	-	-
Precharge power-down with DLL off to commands requiring a locked DLL		t _{XP} DLL	greater of 10nCK or 24ns	-	-
ODT Timing					
RTT turn-on from ODTL on reference		t _{AON}	-225	225	ps
RTT turn-off from ODTL off reference		t _{AO} F	0.3	0.7	t _{CK} (avg)
Asynchronous RTT turn-on delay (power-down with DLL off)		t _{AON} PD	2	8.5	ns
Asynchronous RTT turn-off delay (power-down with DLL off)		t _{AO} FPD	2	8.5	ns
ODT HIGH time with WRITE command and BL8		ODTH8	6	-	nCK
ODT HIGH time without WRITE command or WRITE command and BC4		ODTH4	4	-	nCK
Dynamic ODT Timing					
RTT dynamic change skew		t _{ADC}	0.3	0.7	t _{CK} (avg)
Write Leveling Timing					
First DQS, /DQS rising edge		t _{WLM} RD	40	-	nCK
DQS, /DQS delay		t _{WLD} QSEN	25	-	nCK
Write 20evelling setup from rising CK, /CK crossing to rising DQS, /DQS crossing		t _{WLS}	165	-	ps
Write 20evelling hold from rising DQS, /DQS crossing to rising CK, /CK crossing		t _{WLH}	165	-	ps
Write leveling output delay		t _{WLO}	0	7.5	ns
Write leveling output error		t _{WLOE}	0	2	ns

For part number IMM2G72D3(L)RVD4AG-D125(I)

Table 19 – SPD Information

Byte NO.	Description	Note		Hex	
		1.35V	1.5V	1.35V	1.5V
0	Number of SPD written / SPD Device Size / CRC Coverage	176, 256, 0-116		92	
1	SPD Revision	Revision 1.2		12	
2	Key Byte / DRAM Device Type	DDR3 SDRAM		0B	
3	Key Byte / Module Type	Registered DIMM		01	
4	SDRAM Density and Banks	4Gbits, 8banks		04	
5	SDRAM Addressing	Row 16, Col 11		22	
6	Module Nominal Voltage, V _{DD}	1.35V / 1.5V	1.5V	02	00
7	Module Organization	2 Ranks, 8bits		08	
8	Module Memory Bus Width	ECC, 72bits		0B	
9	Fine Timebase (FTB) Dividend / Divisor	2.5ps		52	
10	Medium Timebase (MTB) Dividend	1ns		01	
11	Medium Timebase (MTB) Divisor	8		08	
12	SDRAM Minimum Cycle Time (t _{CKmin})	1.25ns		0A	
13	Reserved	-		00	
14	CAS Latencies Supported, Least Significant Byte	5, 6, 7, 8, 9, 10, 11		FE	
15	CAS Latencies Supported, Most Significant Byte	-		00	
16	Minimum CAS Latency Time (t _{AAmin})	13.125ns		69	
17	Minimum Write Recovery Time (t _{WRmin})	15ns		78	
18	Minimum RAS# to CAS# Delay Time (t _{RCDmin})	13.125ns		69	
19	Minimum Row Active to Row Active Delay Time (t _{RRDmin})	6ns		30	
20	Minimum Row Precharge Delay Time (t _{RPmin})	13.125ns		69	
21	Upper Nibbles for t _{RAS} and t _{RC}	-		11	
22	Minimum Active to Precharge Delay Time (t _{RASmin}), Least Significant Byte	35ns		18	
23	Minimum Active to Active/Refresh Delay Time (t _{RCmin}), Least Significant Byte	48.125ns		81	
24	Minimum Refresh Recovery Delay Time (t _{RFCmin}), Least Significant Byte	260ns		20	
25	Minimum Refresh Recovery Delay Time (t _{RFCmin}), Most Significant Byte	-		08	
26	Minimum Internal Write to Read Command Delay Time (t _{WTRmin})	7.5ns		3C	
27	Minimum Internal Read to Precharge Command Delay Time (t _{RTPmin})	7.5ns		3C	
28	Upper Nibbles for t _{FAW}	-		00	
29	Minimum Four Activate Window Delay Time (t _{FAWmin})	30ns		F0	
30	SDRAM Optional Features	DLL-Off, RZQ/7, RZQ/6		83	
31	SDRAM Thermal and Refresh Options	ASR, 0°C-95°C, req. 2x Refresh		05	
32	Module Thermal Sensor	Thermal Sensor incorporated		80	
33	SDRAM Device Type	Dual Die Package		A1	
34	Fine Offset for SDRAM Minimum Cycle Time (t _{CKmin})	-0ns		00	
35	Fine Offset for Minimum CAS Latency Time (t _{AAmin})	-0ns		00	
36	Fine Offset for Minimum RAS# to CAS# Delay Time (t _{RCDmin})	-0ns		00	

Byte NO.	Description	Note		Hex	
		1.35V	1.5V	1.35V	1.5V
37	Fine Offset for Minimum Row Precharge Delay Time (t_{RPmin})	-0ns		00	
38	Fine Offset for Minimum Active to Active/Refresh Delay Time (t_{RCmin})	-0ns		00	
39-40	Reserved, General Section	-		00	
41	SDRAM Maximum Activate Count (MAC) Value	8192*tREFI, Untested MAC		00	
42-59	Reserved, General Section	-		00	
60	Raw Card Extension, Module Nominal Height	18<Height<=19 mm		04	
61	Module Maximum Thickness	1 < tF <=2 mm, 1 < tB <=2 mm		11	
62	Reference Raw Card	Raw Card N1		2C	
63	DIMM Module Attributes	1 Row DRAM, 1 Register		05	
64	RDIMM Thermal Heat Spreader Solution	No Heat Spreader incorporated		00	
65-66	Register Manufacturer's JEDEC ID Code	-		00	
67	Register Revision Number	Undefined		FF	
68	Register Type	SSTE32882		00	
69	RC1 (MS Nibble) / RC0 (LS Nibble)	-		00	
70	RC3 (MS Nibble) / RC2 (LS Nibble) – Drive Strength, Command/Address	Strong Drive		A0	
71	RC5 (MS Nibble) / RC4 (LS Nibble) – Drive Strength, Control and Clock	Clock: Moderate Drive, Control: Moderate Drive		55	
72	RC7 (MS Nibble) / RC6 (LS Nibble)	-		00	
73	RC9 (MS Nibble) / RC8 (LS Nibble)	-		00	
74	RC11 (MS Nibble) / RC10 (LS Nibble)	-		00	
75	RC13 (MS Nibble) / RC12 (LS Nibble)	-		00	
76	RC15 (MS Nibble) / RC14 (LS Nibble)	-		00	
77-116	Reserved	-		00	
117-118	Module ID: Module Manufacturer's JEDEC ID Code	I'M		04 9E	
119	Module ID: Module Manufacturing Location	-		00	
120-121	Module ID: Module Manufacturing Date	Manufacturer's data		-	
122-125	Module ID: Module Serial Number	Manufacturer's data		-	
126-127	SPD Cyclical Redundancy Code (CRC)	-		07 31	AC B6
128-145	Module Part Number	Manufacturer's data		-	
146-147	Module Revision Code	-		00	
148-149	DRAM Manufacturer's JEDEC ID Code	-		00	
150-175	Manufacturer's Specific Data	Manufacturer's data		-	
176-255	Open For Customer Use	-		00	

Revision History

Revision	Descriptions	Release Date
1.0	Initial release	May, 2021
2.0	1. Revise Table 5 – Memory Chip Information 2. Revise Table 19 – SPD Information	Jun, 2021

Contents

Features	2
Table 1 - Ordering Information for RoHS Compliant Product	3
Table 2 - Operating Voltage	3
Table 3 – Temperature Grade	3
Table 4 – Speed Grade	3
Table 5 – Memory Chip Information	3
Part Number Decoder	4
Table 6 - Addressing	4
Table 7 - Pin Assignment	5
Table 8 - Pin Description	6
Module Dimension	7
Figure 1 – 240 Pin DDR3 SDRAM VLP Registered DIMM	7
Table 9 - PCB Dimension	7
Figure 2 – Functional Block Diagram (Page 1 of 4)	8
Figure 3 – Functional Block Diagram (Page 2 of 4)	9
Figure 4 – Functional Block Diagram (Page 3 of 4)	10
Figure 5 – Functional Block Diagram (Page 4 of 4)	11
Table 10 - Absolute Maximum DC Ratings	12
Table 11 - DC Electrical Characteristics and Operating Conditions	13
Table 12 - DC Electrical Characteristics and Input Conditions	13
Table 13 - Input Switching Conditions	14
Table 14 - Differential Input Operating Conditions (CK, /CK and DQS, /DQS)	15
Table 15 - Single-Ended Output Driver Characteristics	16
Table 16 - Differential Output Driver Characteristics	16
Table 17 - I _{DD} Specifications with Conditions and Operation Current	17
Table 18 - AC Timing Parameter and Operating Conditions	18
Table 19 - SPD Information	21
Revision History	23
Contents	24
List of Tables	25
List of Figures	25

List of Tables

Table 1 - Ordering Information for RoHS Compliant Product	3
Table 2 - Operating Voltage	3
Table 3 – Temperature Grade	3
Table 4 – Speed Grade	3
Table 5 – Memory Chip Information	3
Table 6 - Addressing	4
Table 7 - Pin Assignment	5
Table 8 - Pin Description	6
Table 9 - PCB Dimension	7
Table 10 - Absolute Maximum DC Ratings	12
Table 11 - DC Electrical Characteristics and Operating Conditions	13
Table 12 - DC Electrical Characteristics and Input Conditions	13
Table 13 - Input Switching Conditions	14
Table 14 - Differential Input Operating Conditions (CK, /CK and DQS, /DQS)	15
Table 15 - Single-Ended Output Driver Characteristics	16
Table 16 - Differential Output Driver Characteristics	16
Table 17 - I _{DD} Specifications with Conditions and Operation Current	17
Table 18 - AC Timing Parameter and Operating Conditions	18
Table 19 - SPD Information	21

List of Figures

Figure 1 – 240 Pin DDR3 SDRAM VLP Registered DIMM	7
Figure 2 – Functional Block Diagram (Page 1 of 4)	8
Figure 3 – Functional Block Diagram (Page 2 of 4)	9
Figure 4 – Functional Block Diagram (Page 3 of 4)	10
Figure 5 – Functional Block Diagram (Page 4 of 4)	11