

W32L100-MRA3FP

32" Marine Display



KEY FEATURES

- High image quality, 1920 x 1080 pixels resolution Marine Display
- 9~36 V DC to DC power input acceptable (Isolation Resistance)
- High quality touchscreen / AR protection glass for option
- Ease of use front panel OSD control Marine Display
- Enhanced shock and vibration resistance
- Panel Mount




SPECIFICATIONS

Display	
Resolution	1920x1080
Contrast Ratio	4000:1
Display Color	16.7M Colors
Active Area	698.4 x 392.85 mm
Size	32 inches
Panel Brightness	400 nits
View Angles	89,89,89,89
Touch / Glass	Projected Capacitive Multi Touch Screen PCAP with With ITO Flim (Optional)
Environment	
Operating Humidity	10% to 95% RH
Storage Temperature	-20°C~60°C
Operating Temperature	-15~55°C
Certification	
Certification	CE, FCC
IO Ports	
USB Port	1 x USB for Touch
Video	1 x VGA 1 x DVI-D 1 x HDMI
Mechanical	
Dimension	825 x 500 x 87.2 mm
Enclosure	Metal Housing with Aluminum Bezel
Cut out	762 x 474 mm
Mounting	VESA Mount/ Rack Mount/ Panel Mount
Cooling System	Fanless Design
Accessory	
Accessory	1 x User Manual(Hardcopy) 1 x Power Cord MIL-DTL-38999/1 1 x VGA Cable 1 x DVI Cable 1 x HDMI
Power	
Power Rating	DC 9~36V, ±10%
Control	
Button	7 key: Power Decrease

Increase
Exit/ Auto
Menu
Day/ Night
Lock/ Unlock

DIMENSIONS UNIT:MM



NOTE

1. This is a simplified drawing and some components are not marked in detail.
2. Please contact our sales representative if you need further product information.
3. All specifications are subject to change without prior notice.
4. The product shown in this datasheet is a standard model. For diagrams that contain customized or optional I/O, please contact the Winmate Sales Team for more information.