

Series 107-50 Aluminum Extractor



CONNECT AND PROTECT

Series 107-50 Aluminum Inserter / Extractor

MATERIALS AND FINISH

Extractor

- **Materials:**
Aluminum alloy 6061-T6
- **Finish:**
Black anodize per Mil-A-8625,
Class 2, Type II or Clear Chemical
Film per Mil-DTL-5541, Class 3,
Type II for a conductive finish.

Assembly Pin

- **Materials:** Stainless steel
- **Finish:** Passivated

APPLICATION DATA


Two inserter or inserter-extractors are recommended per printed circuit board taller than 127 mm (5 in) height.

Detail of Actuating Surfaces

Required on Top and Bottom guide plates

Provides insertion and extraction travel of 8.9 (.35) min.

Nominal position of card edge when seated in connector. The inserter-extractor can move the board an additional 1.3 (.050) if necessary due to the tolerances of the assembly





Units: mm (in)

Unless otherwise specified:

.xx ± .25, .x ± .5

(.xxx ± .010, .xx ± .02)




ASSEMBLY PIN

Option to be pre-started for:

- Faster and easier installation of the extractor to the PCB
- Eliminates the need for special tools or equipment and set up time
- Eliminates loss of loose assembly pins

If the "P" option is not selected, the extractors and the pins will be packaged seperately.



2.38 (.094) dia x 6.35 (.250) long
Pin protrusion of approximately .38 (.015) seeks hole in PCB

Part Number Code

Series 107-50 Inserter/Extractor

Assembly Pin

Loose

Pre assembled

Finish

Black Anodized

Conductive Clear Chem Film

PCB Thickness

1.6 (.063)

2.4 (.094)

3.2 (.125)

P

C

107-50-3

[blank]

P

[blank]

C

[blank]

[blank]

3

4

Part Number Code example: PC107-50-3
Series 107-50 extractor, with pre-started assembly pin, conductive clear chem film finish, for PCB thickness of 2.4 (.094)

CALMARK™

nVent SCHROFF, Inc. 7328 Trade Street, San Diego, CA 92121 USA, +1 800-525-4682



Our powerful portfolio of brands:
CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER